




**60x**  
**60cm | SOLUBLE SALT**



## ABOUT US

Varmora Granito Pvt. Ltd. is a flagship company of the Varmora Group and a leading manufacturer of high-quality ceramic tiles, bath and sanitary products, and other building materials. Established in 1994, Varmora Granito has grown to become one of the largest manufacturers in the industry, with in-house production capacity of 35 msm per annum. With a focus on innovation, sustainability, and customer satisfaction, Varmora Granito is committed to providing its customers with the best products and services worldwide. Varmora now boasts 317 exclusive brand outlets (EBOs) and 2,000+ multi-brand outlets (MBOs) in their network. Whether you're looking for stylish tiles, durable bath and sanitary products, or other building materials, Varmora Granito has you covered.

To know more about Varmora Granito visit [www.varmora.com](http://www.varmora.com)



60x  
60cm




In the world of interior design, **Nano Tiles stand** as a testament to the future, where sophistication and innovation converge. Crafted with precision through the wonders of nano technology, these tiles exemplify elegance, durability, and cutting-edge design. Whether used to grace floors, walls, or other surfaces, Nano Tiles effortlessly merge aesthetics with longevity, promising a timeless visual appeal that endures.







**SASSO** | Finish : Glossy




NANO NIOVE



NANO OLIVINE



NANO SEVILLA




NANO VERSALITE







**SASSO** | Finish : Glossy




NANO GLACIER



NANO ORIONWOOD



NANO CANYON




NANO EMERICO







**SASSO** | Finish : Glossy




NANO DIMAS



NANO KYNE



NANO STREAM




NANO BREZA







**SASSO** | Finish : Glossy




NANO AVARIS



NANO CRETA



NANO BENZ



NANO PEARL IVORY



# Technical Specification

## SOLUBLE SALT (UNGLAZE TILE)

SR. NO.	CHARACTERISTIC	TEST METHOD	IS 15622 :2017 (GROUP B I a)	VARMORA VALUE
<b>A</b>				
<b>DIMENSION &amp; SURFACE QUALITY</b>				
1	Deviation in Length & Width	IS - 13630 - 1	± 0.10%	± 0.10%
2	Deviation in Thickness	IS - 13630 - 1	± 5.00%	± 3.50%
3	Straightness of sides	IS - 13630 - 1	± 0.10%	± 0.10%
4	Rectangularity	IS - 13630 - 1	± 0.10%	± 0.10%
5	Surface Flatness	IS - 13630 - 1	± 0.50%	± 0.20%
6	Surface Quality	IS - 13630 - 1	Minimum 95 % of tiles shall be free from visible defects	95%
<b>B</b>				
<b>PHYSICAL PROPERTIES</b>				
1	Water Absorption	IS - 13630 - 2	≤0.08%,Avg.	0.06%,Avg.
2	Modulus of Rapture(N/mm <sup>2</sup> )	IS - 13630 - 6	Avg. 35 N/mm <sup>2</sup>	Avg. 38 N/mm <sup>2</sup>
3	Breaking Strength (N)	IS - 13630 - 6	Thickness <7.5 mm = 700 N, Min Thickness ≥7.5 mm = 1300 N, Min	Thickness ≥7.5 mm = 1500 N
4	Moisture Expansion (mm/m)	IS - 13630 - 3	0.02 Max.	0.01 Max.
5	Scratch Hardness of Surface (Mohs' Scale)	IS - 13630 - 13	5, Min	5, Min*
6	Resistance of Surface Abrasion (Glazed tiles)	IS - 13630 - 11	Class II, Min.	Class IV
7	Co-efficient of linear thermal expansion	IS - 13630 - 4	6x10 <sup>-6</sup> , Max	6x10 <sup>-6</sup> , Max
8	Thermal Shock Resistance	IS - 13630 - 5	10 Cycles, Min	10 Cycles, Pass
9	Crazing Resistance	IS - 13630 - 9	4 Cycles at 7.5 Bar ,Min	4 Cycles, Pass
10	Impact Resistance- Coefficient of Restitution	IS - 13630 - 14	0.55, Min	0.55, Min
11	Coefficient of Friction	-	Manufacturer Norms	Manufacturer Norms
12	Frost Resistance	IS - 13630 - 10	Manufacturer Norms	No Damage
13	Bulk Density (g/cc)	IS - 13630 - 2	2.2, Min	2.3, Min
<b>C</b>				
<b>CHEMICAL PROPERTIES</b>				
1	Resistance to Staining	IS - 13630 - 7	Class 2, Min	Class 2, Min
2	Resistance to Household Chemicals	IS - 13630 - 8	Class AA,Min	Class AA
3	Resistance to Acids & Alkalis	IS - 13630 - 8	Required If agreed according to chemical resistance class indicated by manufacturer	Resistance

VARMORA Values given above are own valued, Which we tries to maintain, how ever test results may differ up to the limit prescribed under IS 15622 :2017 (GROUP B I a)  
\* Minimum 5 On matt tiles.

Note: Colour shown are as accurate as the limitations of the printing process will allow. Prospective customers are advised to inspect a sample of the tile before ordering. Our effort has been made to ensure the accuracy of the information given. However, the company reserve the right to change the specifications without prior notice. Sometime variations in shade or size being inherent to ceramic industry may occur. Before fixing, we advise you to follow the fixing instructions on the cartons (box) of the tiles. No responsibility will be accepted by the company once the tiles have been fixed.



# VARMORA

TILES • BATHWARE

### HEAD OFFICE

8/A National Highway, At. Dhuva, Tal. Wankaner, Morbi-363621, Gujarat, India

### Tiles Contact:

Mob.: +91 98252 23068

E-mail: marketing@varmora.com

### Bathware Contact:

Mob.: +91 90999 13129

E-mail: marketing@varmorasanitaryware.com

### Mob.: +91 99139 23095

E-mail: customercare.faucets@varmora.com

### Mob.: +91 90990 01734

E-mail: customercare.bathware@varmora.com

### Mob.: +91 90990 01734

E-mail: customercare.sink@varmora.com

### CORPORATE OFFICE

Varmora Granito Pvt. Ltd.  
1004/5/6 South Tower, ONE42  
Off. Bopal-Ambli Road  
Ahmedabad-380054, Gujarat,INDIA

### REGIONAL OFFICE

A-54, 1st Floor, Elite Auto House  
Mathuradas Vasanji Road, Andheri - Kurla Road  
Andheri (East) Mumbai 400 093  
Tel.: +91-22-4973 9179, Fax: +91-22-2838 9794  
E-mail: mumbai@varmora.com

Tiles Customer Care:

**1800 212 0053**

Bathware Customer Care

**1800 212 4525**

Follow us:

