


80x 80cm | DOUBLE CHARGE





ABOUT US

Varmora Granito Pvt. Ltd. is a flagship company of the Varmora Group and a leading manufacturer of high-quality ceramic tiles, bath and sanitary products, and other building materials. Established in 1994, Varmora Granito has grown to become one of the largest manufacturers in the industry, with in-house production capacity of 35 msm per annum. With a focus on innovation, sustainability, and customer satisfaction, Varmora Granito is committed to providing its customers with the best products and services worldwide. Varmora now boasts 317 exclusive brand outlets (EBOs) and 2,000+ multi-brand outlets (MBOs) in their network. Whether you're looking for stylish tiles, durable bath and sanitary products, or other building materials, Varmora Granito has you covered.

To know more about Varmora Granito visit www.varmora.com

80x 80cm



TECHNICAL FEATURES :





NANO TECHNOLOGY

DOUBLE CHARGE COLLECTION

Discover our **Double Charge** vitrified tiles-elegance meets durability. These tiles are the ultimate choice for both indoor and outdoor spaces. With a range of stunning designs, they replicate the beauty of natural materials while boasting a glossy finish.










MATRIX BEIGE










MATRIX CREMA









MATRIX GOLDEN









MATRIX PINK







MARVELOUS | Finish : Glossy




MARVEL WHITE







TROPICANA | Finish : Glossy




FEATHER WHITE







CIVIC | Finish : Glossy



DYNAMIC WHITE







CIVIC | Finish : Glossy



DYNAMIC CREMA

www.**varmora**.com





CIVIC | Finish : Glossy



POLO WHITE







CIVIC | Finish : Glossy



POLO CREMA







FUSION | Finish : Glossy



AVIO DOVE








FUSION | Finish : Glossy



AVIO CREMA







BLOSSOM | Finish : Glossy

BLOSSOM WHITE

Technical Specification

DOUBLE CHARGE

SR. NO.	CHARACTERISTIC	TEST METHOD	IS 15622 :2017 (GROUP B I a)	VARMORA VALUE
	DIMENSION & SURFACE QUALITY			
1	Deviation in Length & Width	IS - 13630 - 1	± 0.10%	± 0.10%
2	Deviation in Thickness	IS - 13630 - 1	± 5.00%	± 3.50%
3	Straightness of sides	IS - 13630 - 1	± 0.10%	± 0.10%
4	Rectangularity	IS - 13630 - 1	± 0.10%	± 0.10%
5	Surface Flatness	IS - 13630 - 1	± 0.50%	± 0.20%
6	Surface Quality	IS - 13630 - 1	Minimum 95 % of tiles shall be free from visible defects	95%
	PHYSICAL PROPERTIES			
1	Water Absorption	IS - 13630 - 2	<u>≤</u> 0.08%,Avg.	0.06%,Avg.
2	Modulus of Rapture(N/mm ²)	IS - 13630 - 6	Avg. 35 N/mm ²	Avg. 38 N/mm ²
3	Breaking Strength (N)	IS - 13630 - 6	Thickness <7.5 mm = 700 N, Min Thickness ≥7.5 mm = 1300 N, Min	Thickness \geq 7.5 mm = 1500 N
4	Moisture Expansion (mm/m)	IS - 13630 - 3	0.02 Max.	0.01 Max.
5	Scratch Hardness of Surface (Mohs' Scale)	IS - 13630 - 13	5, Min	5, Min*
6	Resistance of Surface Abrasion (Glazed tiles)	IS - 13630 - 11	Class II, Min.	Class IV
7	Co-efficient of linear thermal expansion	IS - 13630 - 4	6x10 [€] , Max	6x10 ^{-¢} , Max
8	Thermal Shock Resistance	IS - 13630 - 5	10 Cycles, Min	10 Cycles, Pass
9	Crazing Resistance	IS - 13630 - 9	4 Cycles at 7.5 Bar ,Min	4 Cycles, Pass
10	Impact Resistance- Coefficient of Restitution	IS - 13630 - 14	0.55, Min	0.55, Min
11	Coefficient of Friction	-	Manufacturer Norms	Manufacturer Norms
12	Frost Resistance	IS - 13630 - 10	Manufacturer Norms	No Damage
13	Bulk Density (g/cc)	IS - 13630 - 2	2.2, Min	2.3, Min
	CHEMICAL PROPERTIES			
1	Resistance to Staining	IS - 13630 - 7	Class 2, Min	Class 2, Min
2	Resistance to Household Chemicals	IS - 13630 - 8	Class AA,Min	Class AA
3	Resistance to Acids & Alkalis	IS - 13630 - 8	Required If agreed according to chemical resistance class indicated by manufacturer	Resistance

VARMORA Values given above are own valued, Which we tries to maintain, how ever test results may differ up to the limit prescribed under IS 15622 :2017 (GROUP B I a) * Minimum 5 On matt tiles.

Note: Colour shown are as accurate as the limitations of the printing process will allow. Prospective customers are advised to inspect a sample of the tile before ordering. Our effort has been made to ensure the accuracy of the information given. However, the company resorve the right to change the specifications without prior notice. Sometime variations in state or size being inherent to caramic industry may occur. Before fixing, we advise you to follow the fixing instructions on the caractors. Using the lines. No responsibility will be accepted by the company once the lists have been fixed.



HEAD OFFICE

8/A National Highway, At. Dhuva, Tal. Wankaner, Morbi-363621, Gujarat, India

Tiles Contact:

Mob.: +91 98252 23068 E-mail: marketing@varmora.com

Mob.: +91 99139 23095 E-mail: customercare.faucets@varmora.com

Mob.: +91 90990 01734 E-mail: customercare.sink@varmora.com

CORPORATE OFFICE

Varmora Granito Pvt. Ltd. 1004/5/6 South Tower, ONE42 Off Bopal-Ambli Road Ahmedabad-380054, Gujarat, INDIA

Tiles Customer Care: 1800 212 0053

(E)

Bathware Customer Care 1800 212 4525

Bathware Contact:

Mob.: +91 90999 13129 E-mail: marketing@varmorasanitaryware.com

Mob.: +91 90990 01734

E-mail: customercare.bathware@varmora.com

REGIONAL OFFICE

A-54, 1st Floor, Elite Auto House Mathuradas Vasanji Road, Andheri - Kurla Road Andheri (East) Mumbai 400 093 Tel.: +91-22-4973 9179, Fax: +91-22-2838 9794 E-mail: mumbai@varmora.com

